


Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P: 9210 903 903, +91 129 4272727, © 93111 24302 E: info@prestogroup.com






Box Compression Tester – Digital Cum Computerised (Wintest)





Model No: PBCC - 600 (C)


Box Compression Tester is a consistent tool to indicate the Compression strength of cardboard boxes so that it does not get deformed or crushed when stacked one above the other during storage or transit. PRESTO Box compression Tester is manufactured under various Test Standards ASTM D642, ASTM D4169, TAPPI T804, ISO 12048, and JIS Z0212.





Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P: 9210 903 903, +91 129 4272727, S 93111 24302 E: info@prestogroup.com





Available in Digital model also.

- Microprocessor based display for accurate test results
- Highly accurate test results under uniform compression Force
- Strong base plate with rugged structure
- Bright LED display
- Feather touch controls
- Graph test report is Force Vs Time
- 10 Sample test reports can be seen on one report
- Email facility of report
- Report Available in PDF format
- Pass/Fail Criteria can be programmed
- Easy Data Management. User can create product identification, test details etc.
- Inbuilt hardware/software CD
- ** Computer & Printer are not a part of the offer

The Compression strength is determined by placing the box on a flat platform and pressing it downwards from top with the help of motorized arrangement.

Optional Features:

Digital models also available (with and without printer facility) in various platform sizes and Load Cell Capacity.

The compression strength can be calculated by user by placing the box on a flat platform under compressive force.

Key Specifications:

Display	• LED (Digital)
	Graphical
Accuracy	$\pm 0.5\%$ full scale (with master load)
Power	220V, Single / Three phase, 50 Hz
Test Speed	12.5 ± 2.5 mm/min
Test Method D	After completion test stop automatically
Communication Port	RS 232

Highlights:

Test Report	10 Samples
Peak Hold Facility	Yes
Safety Switch	Upward & Downward Limit Switches
Material	Mild Steel
Finish	Powder coated Havel Gray & Blue combination finish and bright chrome / zinc plating for corrosion resistant finish
Multi Speed	Programmed Test speed / Home Speed feature

* Available in 3 Models of Platform Size : • 450 x 450 mm • 600 x 600 mm • 1000 x 1000 mm.

450 x 450 mm & 600x600 mm Capacity: 500 kgf Model L.C. 200 gm Model 1000 x 1000 mm (1x1 Mtr.) Capacity: 1000 Kgf

Thank you customers for choosing us as your partners in growth!





























*All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.

OUR OTHER PRODUCTS:-







Tensile Tester Digital



Reliance

Spectrocolorimeter



Cobb Sizing Tester



Digital GSM Balance





