

## Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P : 9210 903 903, +91 129 4272727, 🕓 93111 24302 E : info@prestogroup.com

Faridabad • Sonipat • Kolkata • Mumbai • Pune • Ahmedabad
Chennai • Bangalore • Hyderabad

www.prestogroup.com




# Precision Color Matching - TP 110



#### Model No. TP110

**Precision Color Matching TP110** is a consistent tool useful for portable and high quality color measurement. It works with color sensor with multiple channels according to international standards. Color Matching TP110 complies with various CIE Standards.

- Adopts accurate camera locating feature
- Illumination locating for user ease of operation
- Software based output of test results
- Auto white and black calibration
- Various Color Sources
- Display of Whiteness, Yellowness and Color Fastness
- Convenient Operation and ergonomic design
- Small measuring aperture- easy to measure concave-convex object
- Creative Facula locating and cross locating



Top View

Front View

Side View



# Presto Stantest Pvt. Ltd.

I-42, DLF Industrial Area Phase-1, Delhi Mathura Road, Faridabad 121003, Haryana, India P : 9210 903 903, +91 129 4272727, S 93111 24302 E : info@prestogroup.com • Faridabad • Sonipat • Kolkata • Mumbai • Pune • Ahmedabad

• Chennai • Bangalore • Hyderabad

www.prestogroup.com



The portable color measurement instrument is used to measure the color consistency of various types of products and is designed for many production verticals like plastics, rubbers, paper & Packaging, paint & plating, automotive, textile and many more.

#### **Key Specifications:**

Illumination/Observation system	8/d (8° illumination angle/diffuse viewing)
Measuring Aperture	4 mm (Diameter)
Light Sources	D-65
Detector	Silicon photoelectric diode
Color Spaces Indices	CIEL*a*b*C*h;*CIEL*a*b*; CIEXYZ
Minimum Interval Between measurement	Approx 1.0s
Measuring End Face	Large stable end face and small concave convex end face
Repeatability	Standard deviation with in $\Delta E$ * ab0.08 (avg. on 30 measurement with standard white plate.)

#### Highlights:

Battery	Li-on battery3.7 V DC (Lithium Ion,3200mAh)
Lamp Life	3 years approx
Display	2.8 Inch @ 16 : 9 TFT true color
Storage	Upto 20000 samples and 100 standards
Communication Port	USB
Dimensions	205x70x80 mm

#### Standard Accessory :

Power adaptor, Li-ion Battery inbuilt, operating instruction manual, white calibration cover, wrist band, 4 mm measuring aperture, USB cable.

#### **Optional Accessory :**

- Miniature thermal printer
- Other models TP 310, TP 800 also available on request.

#### Thank you customers for choosing us as your partners in growth !



\*All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.

## **OUR OTHER PRODUCTS :-**



### www.prestogroup.com